

Microwave Baking Bags

aka The Potato Bag



The microWAVE Baking Bag

Baked Potatoes in 5 minutes or less

Five simple steps:

1. Wash it, leave it wet
2. Wrap it in a paper towel
3. Put it in the bag
4. Microwave it 4-6 minutes
5. Wrap it in Aluminum foil until ready to eat

PLEASE NOTE: COOKING ONLY ONE POTATO IN BAG MAY CAUSE IT TO OVERHEAT, REDUCE COOK TIME BY 1 MINUTE IF THIS HAPPENS.

- Wash the potatoes and leave moist.
- **DO NOT PIERCE ANY HOLES IN THE POTATO.**
- To keep the bag clean, wrap moist potatoes in a paper towel.
- Place 1 to 3 potatoes, in paper towels, into the bag.
- Close the flap.
To close the flap, pull the flap down towards the bottom of the bag as far as it will go, even if this causes the bag to fold over.
- Cook on high, 4 to 6 minutes depending on the number & size of the potatoes and the power of the microwave.
- **Do Not use the "Baked Potato" button, it will overcook.**

Sweet Potatoes ADD 30 seconds to 1 minute depending on size

Corn in the Husk SUBTRACT 1 minute, soak husk in water and trim hairs before rolling in a paper towel, then placing in bag

After cooking, let the bag air dry.
MACHINE WASHABLE, no fabric softener.

Materials

- 9" x 42" main fabric (or two 9" x 21")
- 8 ½" x 21 ½" cotton batting
- Cotton thread

Construction

1. Use only 100% cotton materials
2. Fold fabric in half, rights sides together. If using two pieces place pieces rights sides together.
3. Lay 100% cotton batting centered on top of fabrics, against wrong side. Pin in place.
4. Mark a 3" are along the center of one short area for an opening.
5. Sew around all four sides just catching the batting in the stitch line, this will be a 3/8" seam allowance. LEAVE OPENING of 3" at markings, along one short edge.
6. Cilp corners and trim any excess batting from the seam allowance. Turn right side out and press, making sure to fold in raw edges along the opening. Top stitch short edge to close; optionally use a decorative stitch for an accent.
7. Measure in 6" from each short end and fold ends towards middle along these marks. Pin in place.
8. Sew both sides closed making sure to back tack both ends AND where the flaps overlap. There needs to be at least 2" of overlap for bag to work.
9. Turn right side out and press.

Wash project before first use.

